



# PATE SPRAY

## MoS<sub>2</sub> PASTE

### DEFINITION

PATE SPRAY is a lubricating paste with molybdenum disulfide in a mineral oil dispersion. PATE SPRAY pretreats surfaces with a thin semi-greasy layer.

### ADVANTAGES

- Creates a safe lubricating coating on all parts and mechanisms.
- Possesses a very low coefficient of friction.
- Stands up well to high temperatures.
- Facilitates disassembly.
- Prevents contact corrosion.
- Bonds well to surfaces.
- Possesses reinforced high pressure power and high load capacity.
- Economical: Requires only a fine spray; applies a uniform product layer.
- Fast and easy to use thanks to the aerosol packaging.
- Reduces frequency of lubricant reapplication.

### APPLICATION FIELDS

- Assembly and running-in plain bearings, runners, gears and more.
- Cold and hot fitting of flanges and main bearings.
- Machining and bracing.
- Pressing tools.

### TECHNICAL CHARACTERISTICS

|  |                        |
|--|------------------------|
| Colour .....                                   | Bluish grey            |
| Density of paste .....                         | 2.1                    |
| Worked penetration at 25°C (NF T 60 132) ..... | 265/295                |
| NLGI Grade .....                               | 2                      |
| 4-balls EP test (ASTM D 2783) .....            | 450 kg                 |
| Operating temperature .....                    | from -40°C up to 450°C |



# TECHNICAL DATA SHEET

## INSTRUCTIONS FOR USE

---

Clean the surface of the part.

Shake the aerosol well. Holding the valve approximately 25 cm away from the part, press straight down on the actuator and spray a fine layer without overloading.

## PACKAGING

---

650ml aerosol

Ref. 4603 A4

x 12

**Manufacturing site and registered office**  
Parc Industriel de la Plaine de l'Ain  
5, allée des Cèdres - 01150 Saint-Vulbas - France  
Tel. +33 (0)4 74 40 20 25 - Fax +33 (0)4 74 40 20 26  
[www.orapi.com](http://www.orapi.com)

**2/2**

TDS 603 / Index 1 – 07/12/2010

ORAPI cannot know about every application for which the products are used nor their conditions of use. ORAPI cannot be held responsible for the suitability of the products for a given use or a specific purpose. The information contained here can on no account be a substitute for the preliminary tests which are essential and which must be carried out in order to check the suitability of the product to each specific case.