

### TECHNICAL DATA SHEET





# **CT 609**

# UNIVERSAL TRANSLUCENT GREASE CLEAN FOOD INDUSTRIES and AGRICULTURE

#### **DEFINITION**

Very high quality translucent grease for use in the food and food-processing industries.

#### **ADVANTAGES**

Complies with **NSF H1 and INS H1** standards for unintentional contact with foodstuffs.

Contains no toxic substances.

Hypoallergenic.

Possesses high mechanical stability and good thermal stability.

Bonds well, infusible (no drop point).

Can be used by centralised lubrication systems.

#### **APPLICATION FIELDS**

O-1---

Lubricate micro-mechanisms, linkages, filters, cylinders, bearings, etc.

Agriculture: lubricate moving parts in tractors, ploughs, etc.

Lubricate mechanisms used in kitchens, food handling devices.

Use in the manufacture and packaging of wine, beer, mineral water, biscuits, meats, fish, and throughout the food-processing industry, in the pharmaceutical industry, paramedical industry, etc.

#### **TECHNICAL CHARACTERISTICS**

Colour	i ransiucent
Texture	Smooth-running liquid
Density at 20°C (NFT 60-101)	0.89
Working temperature	-30°C to +150°C
Drop point (NFT 60-102)	None
Worked penetration after 60 strokes (NFT 60-132)	265/295
NLGI Grade	2
Base oil	Codex-grade
Concentration in sulphur, chlorine, fluorine	< 200 ppm
Copper strip test (NFT 60-135)	1b

Manufacturing site and registered office

- 1/2 -

TDS 609 / Index 2 - 07/20/2013

Parc Industriel de la Plaine de l'Ain 5, allée des Cèdres - 01150 Saint-Vulbas - France Tel. +33 (0)4 74 40 20 20 - Fax +33 (0)4 74 40 20 21 www.orapi-maintenance.com

ORAPI® cannot know about every application for which the products are used nor their conditions of use. ORAPI® cannot be held responsible for the suitability of the products for a given use or a specific purpose.

The information contained here can on no account be a substitute for the

preliminary tests which are essential and which must be carried out in order to

check the suitability of the product to each specific case.



## TECHNICAL DATA SHEET

#### **INSTRUCTIONS FOR USE**

Apply thin, uniform layers on preferably clean surfaces of the mechanisms to be treated.

#### **PACKAGING**

270/200 ml aerosol	Ref. 4609 A8 (mu	ulti-position diffuser)
650 ml	Ref. 4609 A4	x 12
200 g tube	Ref. 3609 T4	x 12
400 g cartridge	Ref. 3609 C4	x 12
400 g Lube Shuttle cartridge	Ref. 3609 CL	x 12
1 kg box	Ref. 3609 B7	x 6
50 kg drum	Ref. 3609 O4	x 1



270/200 ml

#### **AUTHORISATION**



No. 136318 category H1



No. 1795167

check the suitability of the product to each specific case.

ORAPI® cannot know about every application for which the products are used nor